

# alfamax®

LIFE SAVING TECHNOLOGIES

## FIRE ALARM SYSTEMS



[www.alfamax.com.tr](http://www.alfamax.com.tr)

## ADDRESSABLE FIRE ALARM SYSTEMS



**I-1001**  
**Addressable Optical (Photoelectric)  
Smoke Detector**  
Double Led



**I-1003**  
**Addressable Heat Detector**  
Double Led



**I-1053**  
**Addressable Zone Monitor Unit**  
15 Conventional detectors to collect one address



**I-1006**  
**Addressable Sounder**  
allows easy installation



**I-1000-1**  
**1 Loop Addressable Fire Alarm Panel**  
**I-1000-2**  
**2 Loop Addressable Fire Alarm Panel**  
**I-1000-3**  
**3 Loop Addressable Fire Alarm Panel**  
**I-1000-4**  
**4 Loop Addressable Fire Alarm Panel**

- 240x123 Big Screen
- 250x4 Address Capacity
- 32 Zone, 2 Siren Line
- Recessed and surface type mounting options



**I-1000-1R**  
**Repeater Panel**  
Compatible Whit

I-1000-1, I-1000-2, I-1000-3, I-1000-4

Recessed and surface type mounting



**I-1002**  
**Intelligent Multi Sensor**  
Twin LED for 360 vision



**I-1004**  
**Intelligent Ultraviolet Flame  
Detector**  
Detect a 3cm flame at 6 meters.



**I-1050**  
**Addressable Sounder Circuit  
Module**  
Regional siren operating or mute feature



**I-1051**  
**Intelligent Single Input/Output Module**  
Ensures that all relay controls. Available with 220 volts.



**I-1052**  
**Addressable Input Module**  
Be connected device on / of the monitoring and contro module.



**I-1054**  
**Isolator Module**  
be used after each 20 detectors  
Isolates a designated area



**I-1005**  
**Addressable Manual Call Point**  
Addressable Manual Call Point (MCP)  
with re-settable (non breakable) glass



**I-1007**  
**Addressable Natural Gas Detector**  
24 VDC, Relay output

**I-1008**  
**Addressable LPG Gas Detector**  
24 VDC, Relay output

**I-1009**  
**Addressable Carbon Monoxid Gas  
Detector**  
24 VDC, Relay output



**I-1006 F**  
**Addressable Sounder and Strobe**  
Strobe provided by high intensity LED cluster



**AXDZ-01**  
**AX DB-01 Detector Base**  
For I-1001, I-1002, I-1003,  
I-1004 dedectors.

## CONVENTIONAL FIRE ALARM SYSTEMS



**C-1006**  
**Conventional Sounder**  
12V/ 24V/ 220V options.



**C-1006 F**  
**Conventional Sounder and Strobe**  
12V/ 24V/ 220V options.



**R-1002**  
**Relay Multi Sensor  
Smoke + Dual Heat Detector**  
Double Led



**R-1001**  
**Relay Optical Smoke Detector**  
Double led



**R-1003**  
**Relay Heat Increasing Speed Dedektörü**  
normally closed contact N/C For security  
panels 24V and 48V



**C-1007**  
**Natural Gas Detector**  
Gas-controlled, 12 / 24V DC or  
220V AC supply, regional alarm  
signal and relay outputs.



**AXDZ-01**  
**Standard Detector Base**  
For  
C-1002, C1003, C-1004



**ALP-00**  
**Detector Protection Cover**  
Cleaning and the paint effect  
be used for protection be used for protection.



**ALP-01**  
**Remote indicator**  
detector which is used for all types of  
output for indicator.



**C-1000-4 / 4 Zonlu Conventional  
Fire Alarm Panel**  
**C-1000-8 / 8 Zonlu Conventional  
Fire Alarm Panel**  
**C-1000-16/16 Zonlu Conventional  
Fire Alarm Panel**

2 siren outputs, testing and discharge  
day / night mode setting, normal,  
error status, alarm display cases,  
short circuit and open circuit alarm  
and replace the identified regional  
identifying feature of external connec-  
tions, standard relay outputs.



**C-1000-4R / 4 Zonlu Conventional  
Fire Alarm Panel**  
**C-1000-8R / 8 Zonlu Conventional  
Fire Alarm Panel**  
**C-1000-16R / 16 Zonlu Conventional  
Fire Alarm Panel**

2 siren outputs, testing and discharge  
day / night mode setting, normal,  
error status, alarm display cases,  
short circuit and open circuit alarm  
and replace the identified regional  
identifying feature of external  
connections, standard relay outputs.



**C-1002**  
**Conventional Multi Sensor  
Smoke+Heat Detector**  
Double Led




**C-1001**  
**Conventional Optical Smoke Detector**  
Double Led



**C-1004**  
**Conventional Ultraviolet Flame detector**  
Effective range 12 metres



**C-1003**  
**Dual Conventional Heat Detector**  
Double Led



**C-1008**  
**LPG Gas Detector**  
LPG-controlled, 12 / 24V DC or  
220V AC supply, regional alarm  
signal and relay outputs.

**C-1009**  
**Carbonmonoxide Gas Detector**  
Carbonmonoxide controlled,  
12 / 24V DC or 220V AC supply,  
regional alarm signal and relay  
outputs.